


Mechanical Joint Wyes (45° Laterals)

Class 350



Fitting Size (in.)		Dimensions (in.)				Minimum Weight (lbs.)
		T nominal (in.)	T ₁ nominal (in.)	A nominal (in.)	Y nominal (in.)	
Run	Branch					
4"	4"	0.35	0.35	2.50	8.50	45
6"	4"	0.37	0.35	1.50	11.00	66
6"	4"	0.37	0.37	3.00	13.00	91
8"	4"	0.39	0.35	0.50	13.00	93
8"	6"	0.39	0.37	2.00	14.50	116
8"	8"	0.39	0.39	3.50	16.00	130
10"	4"	0.41	0.35	0.00	15.00	114
10"	6"	0.41	0.37	1.00	16.00	141
10"	8"	0.41	0.39	2.50	17.00	177
10"	10"	0.41	0.41	3.50	19.00	189
12"	4"	0.43	0.35	0.00	16.50	210
12"	6"	0.43	0.37	1.50	18.50	174
12"	8"	0.43	0.39	1.50	18.50	235
12"	10"	0.43	0.41	3.00	20.00	275
12"	12"	0.43	0.43	4.50	19.50	248

Class 350

Fitting Size (in.)		Dimensions (in.)				Minimum Weight (lbs.)
		T nominal (in.)	T ₁ nominal (in.)	A nominal (in.)	Y nominal (in.)	
Run	Branch					
14"	14"					474
16"	6"					300
16"	8"					349
16"	12"					453
16"	16"					575
24"	12"					900
24"	18"					1047
24"	24"					1186
30"	24"					1575
36"	36"					2280

NOTE: All fittings on this page - Call for availability